





H100B Handheld Pulse Oximeter

As a handheld pulse oximeter, H100B is designed to serve the needs of both long-term monitoring and spot check. It's dedicated to offer reliable, accurate and sensitive measurement of blood oxygen saturation under even harsh conditions.

Measured Parameters: SpO₂ + PR

300 h SpO₂ Review 100





Easy Operation



Unique Sensor Design



Battery Charger Stand









H100B Handheld Pulse Oximeter Mounting Solutions







Charger Stand

- LCD display with backlight control
- Dual work modes: monitoring & spot check
- Numeric display with plethysmogram display
- Trend review
- Pulse-tone modulation (Pitch Tone)
- Adjustable audio and visual alarms
- Powerful data storage capacity (up to 300 hours)
- PatientCare Viewer software for PC data management
- 4 x AA batteries for up to 48 hours of work

- Rechargeable battery for up to 30 hours of work
- Optional battery charger stand
- Automatic power-off function for power saving

Specification

Classification	
Type of Protection	Internally powered equipment (on battery power)
EMC Compliance	Class B
Degree of Protection	Type BF-Applied Part
Mode of Operation	Continuous
Enclosure Degree of Ingress Protection IPXX	2
Size and Weight	
Size	160 (L)×70 (W)×37.6(H) (mm)
Weight	165 g (without batteries)
Environment	
Temperature	
Working	5 C~40 C
Storage/Shipping	-20 C~55 C
Humidity	
Working	25%~80% (Non-condensing)
Storage/Shipping	25%~93% (Non-condensing)
Display	
H100B	LCD (128*64)
Charger Stand	
Input Voltage	100 to 240 V AC, 50/60 Hz
Output Voltage	8 V DC
Output Current	0.8 A
Output Power	6.4 W

Measuring Parameter Specification Measurement Range 0-100 % SpO₂ 25-300 bpm SpO2 Accuracy Adult (Pediatric) ±2%(70%-100%) ±3%(70%-100%) Neonate Pulse Rate Accuracy Adult/Pediatric ±3 bpm ±3 bpm Neonate SpO₂ Resolution 1% PR Resolution 1 bpm

